

Two stage side feeding plastic recycling machine			
	100i	125i	
Side feeding motor	5HP / 3.7kW	7½HP / 5.6kW	
Extrusion capacity (kg/hr)	200~300	300~450	
Main extruder	Screw diameter (mm)	Ø100	Ø125
	Motor	125HP / 93kW	150HP / 112kW
Sub extruder	Screw diameter (mm)	Ø125	Ø150
	Motor	40HP / 30kW	75HP / 56kW
Hot die-face cutting device	Cutter motor	3HP / 2.2kW	5HP / 3.7kW
	Pump motor	3HP / 2.2kW	5HP / 3.7kW
Hydraulic screen changer motor	5HP / 3.7kW	7½HP / 5.6kW	
Vibrating screener	1/4HP × 2 sets	1/3HP × 2 sets	
Blower	5HP / 3.7kW	5HP / 3.7kW	
Centrifugal dryer	7½HP / 5.6kW	7½HP / 5.6kW	
Silo capacity	500L	600L	

150i	175i
7½HP / 5.6kW	10HP / 7.5kW
450~600	700~900
Ø150	Ø175
200HP / 149kW	300HP / 224kW
Ø180	Ø200
100HP / 75kW	150HP / 112kW
7½HP / 5.6kW	7½HP / 5.6kW
5HP / 3.7kW	7½HP / 5.6kW
7½HP / 5.6kW	10HP / 7.5kW
1/3HP × 2 sets	1/2HP × 2 sets
7½HP / 5.6kW	10HP / 7.5kW
10HP / 7.5kW	15HP / 11kW
800L	1000L